

ADEY MAGNA CLEAN® INDUSTRIAL

For applications in industry, trade and commerce



Technical specifications

ADEY MagnaClean® Industrial

MagnaClean®	Industrial DN 50	Industrial DN 80	Industrial DN 100	Industrial DN 150	Industrial DN 200
Order number	CP1-03-01123	CP1-03-01124	CP1-03-01125	CP1-03-01126	CP1-03-02147
Max. flow rate	64 m³/h	100 m³/h	102 m³/h	108 m³/h	112 m³/h
Max. operating pressure	10 bar	10 bar	10 bar	10 bar	10 bar
Max. operating temp.	100 °C	100 °C	100 °C	100 °C	100 °C
Connection Flange	DN 50	DN 80	DN 100	DN 150	DN 200

✓ Exceptionally powerful magnetic filter unit designed for a wide range of demanding industrial, commercial and commercial applications.

- **Industry**
Factories and production facilities
- **Trade**
Office complexes, public buildings and leisure centers
- **Residential area**
Blocks of flats, big buildings, housing estates
- **Health**
Hospitals, care centers, medical offices, homes for the elderly and nursing homes
- **Leisure**
Sports centres, swimming pools, holiday complexes, hotels and cinemas
- **Education**
Universities, vocational schools and primary and secondary schools
- **Community**
Churches, cathedrals, municipal and public buildings