

# HEATY EB SET LIGHT

Initial filling set with a cartridge, a refill cartridge Complete XL and a flow limiter



## Heaty EB Set Light

The initial filling set „Heaty EB Set Light“ serves as a complement to the replenishment station „Heaty Complete Home“, with which the make-up water is being treated pursuant to VDI 2035. With the new initial filling set now you can also use the replenishment station for the initial filling of small filling systems.

The decisive advantage is a developed controller that can be quickly and easily inserted into the housing head as a plug-in. This prevents high flow velocities. This is a cost-effective way for the skilled tradesman to carry out the initial filling, which he can do without a large start-up investment.

### Your advantages

- ✓ Complement to the replenishment station
- ✓ Compliance with current standards
- ✓ Suitable for initial filling
- ✓ Quick installation of the flow limiter
- ✓ Cost-effective initial filling
- ✓ Low start-up investment

## Content

- ✓ Cartridge
- ✓ Refill cartridge XL
- ✓ Flow limiter

## Technical Data

Max. operating temperature	45 °C
Max. operating pressure	8 bar
Pipe connection	1/2"
Height / width (approx.)	571 / 133 mm
Content	1,5 l
Max. flow rate	3 l/min
Max. filling performance	180 l/h
Capacity for 420 µS/cm to < 100 *	225 l
Art.-No.	100336

\* Note:  
The capacity depends on various parameters like the water temperature, the chemical composition of the water or the flow pressure. For an exact determination a water analysis of the raw water must be carried out. The values given here always refer to the optimum case and do not represent a binding assurance.

