

# HEATY COMPLETE FIX LED-SERIE

Make-up solution for systems from 400 litres up



## Including

- Replenishment cartridge (Composite of Fix-series)
- Filling combination BA
- Water meter, shut-off fittings
- Sieve seal against resin ingress
- LED measuring cell
- Integrated flow limiter (pressure-independent)

## Technical data

Order number 100345  
Order number 100345-OFK

## Heaty Complete Fix Mini LED + OFK

Max. filling performance*	360 l/h
Max. operating pressure	8 bar
Max. operating temperature	50 °C
Height / Width in mm (appr.)	655 / 550 mm
Weight (appr.)	8,3 kg
Mixed bed contents	6 l
Capacity for 420 µS to < 100**	900 l
Electricity connection required	Yes, for LED

The **Heaty Complete Fix LED**-series is a fully pre-assembled replenishment station! It is used when the system is larger than 400 litres and no system separator is available on site.

## Your advantages

- ✓ Ideal for large filling quantities from 400 litres upwards
- ✓ Comply with VDI 2035, ÖNORM H 5195-1 and SWKI BT 102-1 standards
- ✓ Easy handling
- ✓ Safety due to LED measurement



\* Depends on system and network pressure.

\*\* The capacity data are based on the ideal case. Misapplication, water quality and temperature may lead to deviations.



# HEATY COMPLETE FIX LED-SERIE

Make-up solution for systems from 400 litres up



## Including

- Replenishment cartridge (Composite of Fix-series)
- Filling combination BA
- Water meter, shut-off fittings
- Sieve seal against resin ingress
- LED measuring cell
- Integrated flow limiter (pressure-independent)

## Technical data

Order number 100346  
Order number 100346-OFK

## Heaty Complete Fix Small LED + OFK

Max. filling performance*	600 l/h
Max. operating pressure	8 bar
Max. operating temperature	50 °C
Height / Width in mm (appr.)	625 / 550 mm
Weight (appr.)	11,3 kg
Mixed bed contents	9,5 l
Capacity for 420 µS to < 100**	1.350 l
Electricity connection required	Yes, for LED

The **Heaty Complete Fix LED**-series is a fully pre-assembled replenishment station! It is used when the system is larger than 400 litres and no system separator is available on site.

## Your advantages

- ✓ Ideal for large filling quantities from 400 litres upwards
- ✓ Comply with VDI 2035, ÖNORM H 5195-1 and SWKI BT 102-1 standards
- ✓ Easy handling
- ✓ Safety due to LED measurement



\* Depends on system and network pressure.

\*\* The capacity data are based on the ideal case. Misapplication, water quality and temperature may lead to deviations.



# HEATY COMPLETE FIX LED-SERIE

Make-up solution for systems from 400 litres up



## Including

- Replenishment cartridge (Composite of Fix-series)
- Filling combination BA
- Water meter, shut-off fittings
- Sieve seal against resin ingress
- LED measuring cell
- Integrated flow limiter (pressure-independent)

## Technical data

Order number 100347  
Order number 100347-OFK

## Heaty Complete Fix Big LED + OFK

Max. filling performance*	1.200 l/h
Max. operating pressure	8 bar
Max. operating temperature	50 °C
Height / Width in mm (appr.)	775 / 550 mm
Weight (appr.)	20,6 kg
Mixed bed contents	23 l
Capacity for 420 µS to < 100**	3.420 l
Electricity connection required	Yes, for LED

The **Heaty Complete Fix LED**-series is a fully pre-assembled replenishment station! It is used when the system is larger than 400 litres and no system separator is available on site.

## Your advantages

- ✓ Ideal for large filling quantities from 400 litres upwards
- ✓ Comply with VDI 2035, ÖNORM H 5195-1 and SWKI BT 102-1 standards
- ✓ Easy handling
- ✓ Safety due to LED measurement



\* Depends on system and network pressure.

\*\* The capacity data are based on the ideal case. Misapplication, water quality and temperature may lead to deviations.



# HEATY COMPLETE FIX LED-SERIE

Make-up solution for systems from 400 litres up



## Including

- Replenishment cartridge (Composite of Fix-series)
- Filling combination BA
- Water meter, shut-off fittings
- Sieve seal against resin ingress
- LED measuring cell
- Integrated flow limiter (pressure-independent)

## Technical data

Order number 100348  
Order number 100348-OFK

## Heaty Complete Fix Tall LED + OFK

The **Heaty Complete Fix LED**-series is a fully pre-assembled replenishment station! It is used when the system is larger than 400 litres and no system separator is available on site.

Max. filling performance*	2.400 l/h
Max. operating pressure	8 bar
Max. operating temperature	50 °C
Height / Width in mm (appr.)	1.315 / 550 mm
Weight (appr.)	37,4 kg
Mixed bed contents	46 l
Capacity for 420 µS to < 100**	6.840 l
Electricity connection required	Yes, for LED

## Your advantages

- ✓ Ideal for large filling quantities from 400 litres upwards
- ✓ Comply with VDI 2035, ÖNORM H 5195-1 and SWKI BT 102-1 standards
- ✓ Easy handling
- ✓ Safety due to LED measurement



\* Depends on system and network pressure.

\*\* The capacity data are based on the ideal case. Misapplication, water quality and temperature may lead to deviations.

