

HEATY PROFILINE SERIE

Complete unit for professional bypass treatment, magnetit filtration and filtration in the hot water area (up to 80 °C)



Free of charge
instruction on site

Including

- Composite tank (filled with 23 litre mixed bed Vadion pH-Control)
- Stainless steel filter case (1 µm)
- Water meter, 3 filter bags, shut-off fittings
- Removal tap for control
- Funnel for easy refilling
- Integrated flow limiter
- Carrier handle
- Non-return valve
- Sieve seal against resin ingress
- LED measuring cell

These components are completely assembled on sack trucks, incl. Magna-Clean@Professional2XP, hot water pump (max. 4,8 m³/h) and hose set.

Technische Daten

Order number 100455
Order number replacement filter 100454

Heaty Profiline 100

for combined application Filtration and treatment		for single application Filtration	
Max. filling performance*	1.200 l/h	Max. pump performance	4.800 l/h
Min. flow pressure	1,5 bar		
Max. operating pressure	6 bar		6 bar
Max. operating temperature	80 °C		90 °C
Height / Width / Depth (appr.)	1.150 / 500 / 560		1.150 / 500 / 560
Weight (appr.)	47,2 kg		
Mixed bed contents	23 l		
Capacity for 420 µS/cm to < 100**	3.420 l		
Electricity connection required	Yes, for LED and pump		Yes, for pump

Your advantages

- ✓ Pre-installed unit for professional bypass treatment and filtration
- ✓ Safe, simple and flexible bypass treatment
- ✓ Magnetite filtration through built-in magnetic filter
- ✓ System independent due to integrated hot water pump

* Depends on system and network pressure.

** The capacity data are based on the ideal case. Misapplication, water quality and temperature may lead to deviations.



HEATY PROFILINE SERIE

Complete unit for professional bypass treatment, magnetit filtration and filtration in the hot water area (up to 80 °C)



Free of charge
instruction on site

Including

- Stainless steel container (filled with 46 litre mixed bed Vadion pH-Control)
- Stainless steel filter case (1 µm)
- Water meter, 3 filter bags, shut-off fittings
- Removal tap for control
- Funnel for easy refilling
- Integrated flow limiter
- Carrier handle
- Non-return valve
- Sieve seal against resin ingress
- LED measuring cell

These components are completely assembled on sack trucks, incl. Magna-Clean®Professional2XP, hot water pump (max. 4,8 m³/h) and hose set.

Technical data

Order number 100456
Order number replacement filter 100454

Heaty Profiline 200

for combined application Filtration and treatment		for single application Filtration	
Max. filling performance*	2.400 l/h	Max. pump performance	4.800 l/h
Min. flow pressure	1,5 bar		
Max. operating pressure	6 bar		6 bar
Max. operating temperature	80 °C		90 °C
Height / Width / Depth (appr.)	1.350 / 500 / 560 mm		1.350 / 500 / 560 mm
Weight (appr.)	79 kg		
Mixed bed contents	46 l		
Capacity for 420 µS/cm to < 100**	6.840 l		
Electricity connection required	Yes, for LED and pump		Yes, for pump

Your advantages

- ✓ Pre-installed unit for professional bypass treatment and filtration
- ✓ Safe, easy and flexible bypass treatment
- ✓ Magnetite filtration through built-in magnetic filter
- ✓ System independent due to integrated hot water pump

* Depends on system and network pressure.

** The capacity data are based on the ideal case. Misapplication, water quality and temperature may lead to deviations.

