

HEATY RACUN 300 ADVANCED: THE FILLING DEVICE THAT THINKS ALONG

Complete unit for professional bypass treatment, permanent magnetite filtration and monitoring of the conductivities in the water circuit

Suitable for cooling and heating circuits



Heaty Racun-Series

(Mobile filling device with an automatic switch-off when the desired water quality is reached)

In large residential complexes and industrial buildings there are often disturbances due to contaminated system water. The treatment of the water usually takes several days to weeks in which the specialist has to go to the place of operation every day.

Our **Heaty Racun** provides remedy. The **Heaty Racun** is only connected at the place of use and he'll do the rest alone.

As soon as the water quality meets the set parameters it switches off automatically.

If the water quality deteriorates again, the **Heaty Racun** will automatically switch on to direct a partial flow of the system water through the treatment plant via the installed changeover valve.

Your advantages

- ✓ Improvement of the system water quality in existing plants using the bypass treatment
- ✓ Bypass treatment of the system water after initial filling with city water
- ✓ Compliance with current country standards like VDI 2035, Ö-NORM H 5195-1 and SWKI BT 102-1
- ✓ Ideal solution for use in construction phases (e.g. boiler house and pipe network)
- ✓ Fast and flexible application (condition: two options of connection)
- ✓ Magnetite filtration through built-in magnetic filter
- ✓ Permanent monitoring of the conductivities in the plant and automatic processing at limit value transgression
- ✓ Optional: Automatic replenishment in case of pressure loss in conjunction with a system separator
- ✓ Leakage protection by adjustable replenishment water quantity via impulse water meter
- ✓ Automatic switch-off and alarm to central building control system via potential-free output when mixed bed is used up



HEATY RACUN 300 ADVANCED

Complete unit for professional bypass treatment, permanent magnetite filtration and monitoring of the conductivities in the water circuit

Easy to operate and fully electronic control with a display of the respective operating conditions



Fully electronic control

- ✓ Digital display of the measured values in a large and clear display
- ✓ LED display of the operating states in the flow chart
- ✓ Freely selectable limit values for leakage quantities and conductivities in the heating circuit
- ✓ Message when mixed bed resin is used up
- ✓ Central safety switch for switching on and off

The device at a glance

- Ideal for plant sizes from 20 m³
- 1µ filtration for high water purity requirements
- Differential pressure measurement as visible control for the state of depletion of the filter unit
- Adjustable flow rate
- To increase the capacity for larger initial fillings, the device can also be operated with several composite containers.
- Fixed installation for sustainable plant operation
- Storing of work history on SD card

Technical data

	Heaty Racun 300 Advanced
Max. filling performance (approx.)*	3,000 l/h
Ø filling performance in the bypass process (approx.)	adjustable from 1,800 up to 7,200 l/h
Max. operating temperature	80 °C
Weight (approx.)	82 kg
Mixed bed contents	63 l
Capacity for 420 µS/cm to < 100**	9,360 l
Power supply	230 V
Order number	100474-SL

* Depending on system pressure and mains pressure..

** The capacity figures are based on the ideal case.
There may be variations due to errors in usage, water quality and temperature.

